

Filo ottone (Special Wire)

Filo Ottone		Carico di rottura
Kg.	Codice	490/500 N/mm2
Kg.3,8 	0205649 DIN/125	DIA 0,20 mm
	0255649 DIN/125	DIA 0,25 mm
	0305649 DIN/125	DIA 0,30 mm
Kg.8 	0205649 DIN/160	DIA 0,20 mm
	0255649 DIN/160	DIA 0,25 mm
	0305649 DIN/160	DIA 0,30 mm
Kg.16 	0205649 DIN/200	DIA 0,20 mm
	0255649 DIN/200	DIA 0,25 mm
	0305649 DIN/200	DIA 0,30 mm
Kg.25 	0205649 DIN/250	DIA 0,20 mm
	0255649 DIN/250	DIA 0,25 mm
	0305649 DIN/250	DIA 0,30 mm
Kg.45 	0255649 DIN/335	DIA 0,25 mm
	0305649 DIN/335	DIA 0,30 mm
Kg.6 	0205649 P-5	DIA 0,20 mm
	0255649 P-5	DIA 0,25 mm
	0305649 P-5	DIA 0,30 mm
Kg.10 	0205649 P-10	DIA 0,20 mm
	0255649 P-10	DIA 0,25 mm
	0305649 P-10	DIA 0,30 mm
Kg.20 	0205649 P-15	DIA 0,20 mm
	0255649 P-15	DIA 0,25 mm
	0305649 P-15	DIA 0,30 mm

Filo Ottone		Carico di rottura
Kg.	Codice	900 N/mm2
Kg.3,8 	0205690 DIN/125	DIA 0,20 mm
	0255690 DIN/125	DIA 0,25 mm
	0305690 DIN/125	DIA 0,30 mm
Kg.8 	0205690 DIN/160	DIA 0,20 mm
	0255690 DIN/160	DIA 0,25 mm
	0305690 DIN/160	DIA 0,30 mm
Kg.16 	0205690 DIN/200	DIA 0,20 mm
	0255690 DIN/200	DIA 0,25 mm
	0305690 DIN/200	DIA 0,30 mm
Kg.25 	0205690 DIN/250	DIA 0,20 mm
	0255690 DIN/250	DIA 0,25 mm
	0305690 DIN/250	DIA 0,30 mm
Kg.45 	0255690 DIN/335	DIA 0,25 mm
	0305690 DIN/335	DIA 0,30 mm
Kg.6 	0205690 P-5	DIA 0,20 mm
	0255690 P-5	DIA 0,25 mm
	0305690 P-5	DIA 0,30 mm
Kg.10 	0205690 P-10	DIA 0,20 mm
	0255690 P-10	DIA 0,25 mm
	0305690 P-10	DIA 0,30 mm
Kg.20 	0205690 P-15	DIA 0,20 mm
	0255690 P-15	DIA 0,25 mm
	0305690 P-15	DIA 0,30 mm

Esempio di ordinazione/Order example: 0205649 DIN/125 (codice)