

Filo ottone (Techno Brass)

Filo Ottone		Carico di Rottura
Kg.	Codice	1000-1200 N/mm2
 Kg.3,8	0255790 DIN/125	DIA 0,25 mm
	0305790 DIN/125	DIA 0,30 mm
 Kg.8	0255790 DIN/160	DIA 0,25 mm
	0305790 DIN/160	DIA 0,30 mm
	0335790 DIN/160	DIA 0,33 mm
	0365790 DIN/160	DIA 0,36 mm
 Kg.16	0255790 DIN/200	DIA 0,25 mm
	0305790 DIN/200	DIA 0,30 mm
	0335790 DIN/200	DIA 0,33 mm
	0365790 DIN/200	DIA 0,36 mm
 Kg.25	0255790 DIN/250	DIA 0,25 mm
	0305790 DIN/250	DIA 0,30 mm
	0335790 DIN/250	DIA 0,33 mm
	0365790 DIN/250	DIA 0,36 mm

Filo Ottone		Carico di Rottura
Kg.	Codice	1000-1200 N/mm2
 Kg.45	0255790 DIN/335	DIA 0,25 mm
	0305790 DIN/335	DIA 0,30 mm
	0335790 DIN/335	DIA 0,33 mm
	0365790 DIN/335	DIA 0,36 mm
 Kg.6	0255790 P-5	DIA 0,25 mm
	0305790 P-5	DIA 0,30 mm
 Kg.10	0255790 P-10	DIA 0,25 mm
	0305790 P-10	DIA 0,30 mm
	0335790 P-10	DIA 0,33 mm
	0365790 P-10	DIA 0,36 mm
 Kg.20	0255790 P-15	DIA 0,25 mm
	0305790 P-15	DIA 0,30 mm
	0335790 P-15	DIA 0,33 mm
	0365790 P-15	DIA 0,36 mm

Esempio di ordinazione/Order example: 0255790 DIN/125 (Codice)